



CHECKER MOTORS CORP.
KALAMAZOO, MICH.

MODELS A 9 A10 A9L A10L

LUBRICATION CHART

No.	U.S. I.	No. of Pieces	Lubricant	Total Capacity	Check Periods	Remarks
1	ENGINE	1	ENGINE OIL - S.A.E. 10 W. SUPPLEMENT 1 TYPE	5 QTS. TO REFILL	ONLY	DRAIN AND REFILL EVERY 2,000 MILES
2	TRANSMISSION - AUTOMATIC	1	TYPE A - SUFFIX A TRANSMISSION FLUID	12 QTS. TO REFILL	EVERY 1,000 MILES	DRAIN AND REFILL EVERY 15,000 MILES
3	DIFFERENTIAL - EXCEPT POWR-LOK	1	E. P. HYPOID GEAR LUBE - S.A.E. #90	3 LBS. TO REFILL	EVERY 1,000 MILES	CHANGE EVERY 15,000 MILES
3a	DIFFERENTIAL - POWR-LOK	1	LUBRICANT OF THE API-GL-4 TYPE INCORPORATING ADDITIVES SUITABLE FOR USE IN THE POWR-LOK DIFFERENTIAL	3 LBS. TO REFILL	EVERY 1,000 MILES	CHANGE EVERY 15,000 MILES
4	STEERING GEAR	1	E. P. HYPOID GEAR LUBE - S.A.E. #90	/ 12 QTS. TO REFILL	EVERY 2,000 MILES	OIL FLUID IN HOUSING COVER
5	POWER STEERING PUMP	1	TYPE A - SUFFIX A TRANSMISSION FLUID	2 QTS. TO REFILL	EVERY 2,000 MILES	ADD FLUID TO COVER ELEMENT IN RESERVOIR
6	WHEEL BEARING - FRONT	2	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	EACH 1 LB. APPROX.	EVERY 10,000 MILES	REMOVE WHEEL, CLEAN AND REPACK
7	WHEEL BEARING - REAR	2	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	AS REQUIRED	EVERY 10,000 MILES	PRESSURE FITTINGS - DO NOT OVERLOAD
8	UNIVERSAL	3	MINERAL BASE OIL - S.A.E. #100	AS REQUIRED	EVERY 1,000 MILES	PRESSURE FITTINGS
9	SLIP JOINT - PROPELLER SHAFT	1	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	AS REQUIRED	EVERY 2,000 MILES	PRESSURE FITTING
10	BEARING - CLUTCH THROWOUT (Standard)	1	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	AS REQUIRED	EVERY 2,000 MILES	PRESSURE FITTING - THRU HOLE IN PAN UNDERNEATH
11	CROSS SHAFT - CLUTCH THROWOUT (Standard)	1	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	AS REQUIRED	EVERY 2,000 MILES	PRESSURE FITTING
12	STEERING KNUCKLE BALL JOINT	4	ALUMINUM SOAP BASE GREASE	AS REQUIRED	EVERY 2,000 MILES	RELIEVE LOAD AND SWING WHEELS WHILE LUBRICATING
13	AIR CLEANER - DRY TYPE	1	C A U T I O N: KEEP OIL FROM ELEMENT	NONE	EVERY 4,000 MILES	REMOVE: CLEAN CARTRIDGE BY TAPPING GENTLY
14	GEAR SHIFTER	1	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	AS REQUIRED	EVERY 2,000 MILES	PRESSURE FITTING IN LEVER
15	STEERING LINKAGE	5	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	AS REQUIRED	EVERY 2,000 MILES	PRESSURE FITTING - LIGHTLY
16	CLUTCH THROWOUT YOKE (Standard)	1	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	AS REQUIRED	EVERY 2,000 MILES	PRESSURE FITTING
17	OIL BREATHER CAP	1	ENGINE OIL	2 OR 3 DROPS	EVERY 2,000 MILES	WASH IN KEROSENE AND REFILL
18	DISTRIBUTOR ROTOR - FELT (Standard)	1	ENGINE OIL	21 LBS. TO REFILL	EVERY 1,000 MILES	CHANGE EVERY 15,000 MILES
19	TRANSMISSION MANUAL SHIFT (Standard)	1	MINERAL BASE GEAR OIL - S.A.E. 90 WINTER - 140 SUMMER	FEW DROPS	EVERY 2,000 MILES	OIL CUP ON EACH END - WITH OIL CAN
20	PARKING BRAKE LEVER	1	RUST INHIBITED - LITHIUM BASE, ALL-PURPOSE GREASE	FEW DROPS	EVERY 2,000 MILES	OIL CUP ON SIDE - WITH OIL CAN
21	GENERATOR	2	ENGINE OIL	KEEP FILLED	EVERY 2,000 MILES	UNDER HOOD
22	DISTRIBUTOR	1	ENGINE OIL	FEW DROPS	EVERY 2,000 MILES	WITH OIL CAN
23	MASTER CYLINDER MISC. HINGES, ACCEL. LINKAGE PINS, BRAKE AND CLUTCH CONTROL PINS, ETC.	1	BRAKE FLUID - S.A.E. 70-83 - SPECIFICATION MACHINE OIL	FEW DROPS	EVERY 2,000 MILES	

