

TO: J. Stout, G. Orwig, R. Fuller, S. Wilson, S. Hori, E. Horrigan, F. Leamy(3)
R. McCulfor, A. Radke(3) W. Asselin, R. Smith, A. Goedhart, C. Ayres
E. Nelson, C. Cornwell, S. Megyesi, B. Herrington(8) R. Bach, D. Markin
F. Baldwin, J. Copeland, J. Coleman, T. Bedard, K. Bothe, L. Hilsky(4)
J. Temple (4) W. Van Horn

FROM: S. Hori

SUBJECT: SPECIFIC REQUIREMENTS FOR NEW YORK CABS

1. Front Seat Requirements

- a. Front seat back cover must be pulled tight in the lower area to obtain a minimum of 18" for the cushion depth.
- b. A minimum of 18" Rear Seat Cushion depth and a minimum of 28" from the back of the front seat (with the seat adjuster in full back position) to the front edge of the Rear Seat Cushion must be maintained.
Change C must be incorporated in part No. 640172
Support-Manual Seat Adjuster and the Front Seat Assembly moved forward 1" by the use of the added holes

2. Auxiliary Seat Requirements

- a. A 14" wide seat is required
Use 640035 Pad-Aux. Seat Cushion as soon as available
- b. Maintain a minimum of 6-1/2" from the rear of the new 14" auxiliary Seat Pad to the front edge of the rear seat cushion.
Change D must be incorporated in part No. 630435
Hinge - Auxiliary Seat Leg-Female to make the seat position upright.

3. Roof Lamp Wiring

- a. An additional wire is required to the Roof Lamp.
Production is to add an additional 641404 Wire Assem-Driver's Dome Lamp, connecting it to the auxiliary wire (dark blue) at the rear pillar and pass it through the roof along with the regular roof lamp wire no. 641405. Sales will specify B/M grp. no. B-183 for New York jobs.
- b. Instructions for New York installation
Plug the wire for the Off Duty Switch into the socket opposite the Dark Blue auxiliary wire in the right hand 6 way connector under the instrument panel.
The light blue wire thru the roof is the "Taxi" light and the yellow wire is the Off Duty Light.

4. New Card Case with 2 Lamps

- a. Use as soon as available per Eng. Memo. #75